



Server technology geared for performance.

The MPC NetFRAME® 3610 is the performance-driven, affordable server solution workgroups demand. Powerful, reliable, and easily deployed, it delivers the scalability you need for increased growth and productivity. The NetFRAME 3610 server features dual Intel® Xeon® processor technology for superior speed and performance, and hot-swap components to give you flexibility and keep downtime to a minimum. We've also designed the NetFRAME 3610 with plenty of headroom for your growing business. Plus, it's all backed by MPC's award-winning service and support.



NetFRAME® 3610

Server

Processor	Up to two Intel® Xeon processors w/512KB L2 Advanced Transfer Cache and Hyper-Threading Support (NOCONA ready)	
System Bus	533MHz	
Memory	Six DIMM sockets supporting ECC 2-way interleave PC2100 DDR 266 SDRAM 256MB to 12GB*	
Chipset	Intel E7501	
Drive Bays	Up to 10 hot-swap SCSI bays (enabling up to 1.46TB internal storage); plus three external 5.25" & one 3.5" floppy	
Controller	Integrated Dual Channel U320 SCSI	
Graphics	Integrated ATI Rage XL SVGA PCI video controller with 8MB video memory	
Network Interface	Integrated Dual Gigabit Ethernet (10/100/1000) (82546EB)	
Built-in I/O	Two serial ports (one server management port or LAN); One 25-pin parallel port; One SCSI knockout port for external connections; One Video port—SVGA; Four USB Ports; Mini-DIN keyboard and mouse ports	
Expansion Slots	Triple-Peer Bus Architecture with six full-length PCI/PCI-X slots (two 64-bit/100 MHz, one 64-bit/133MHz) (three 32-bit/33MHz PCI slots)	
Power Supply	450W to 650W, dual-line cord 2+1 PFC; 100-127 / 200-240V AC; redundant N+1 hot-swap power supplies; Two power cords per system	
Fans	Supports total of 7: Five system fans, two power supply fans	
Server Management	IPMI 1.5 Compliant; Intel Server Management version 5.5	
System Weight	35.27 lbs. (16KG)	
Chassis	Rack or Pedestal 5U with option of eliminating power redundancy	
System Dimensions	Pedestal:	Rack:
	Height: 17.5"	5U 8.6"
	Width: 8.6" (12.6 w/base)	16.9"
	Depth: 26.9"	24.9" (25.6" w/handles)
Acoustic Emissions	Sound level: <50 dBA (base configuration)	
Operating Temperature	10 degrees C to 35 degrees C	
Electrostatic Discharge	15kV	
Electromagnetic Capability	FCC Part 15, Class A (US) ICES-003, Class A (Canada)	
Safety	UL 60950 - CSA 60950 (US/Canada)	
System Security	Startup password; Flexible disk drive, CD ROM, and hard disk drive boot disable; Power and reset switch lock; Enable or disable serial port, parallel port, flexible disk drive, and write operations to the flexible disk drive; Hot-swap hard disk drive cage lock; Lockable chassis; Chassis Intrusion Detection	
Standard Warranty and Service Offerings	3-Year Limited Parts Warranty & Technical Support Policy; 3-Year On-site Service; 3 Network Operating System (NOS) Resolutions	
	*using 2GB modules	

©2003 MPC Computers, LLC. All rights reserved. MPC Computers, LLC is not responsible for omissions or errors in typography or photography. All purchases are subject to availability. Prices and specifications may be changed without notice; prices do not include shipping and handling and any applicable taxes, unless specifically required to be included under applicable contract. Seller's return policy does not include return freight and original shipping/handling charges, and all return and warranty periods begin from the date a product is shipped, not when it arrived. A restocking fee may be charged upon the return of a product. All sales are controlled by seller's current terms and conditions of sale, and contract terms and conditions as applicable. Copies of seller's terms and conditions of sale and contract terms are available on seller's website or from its sales representatives. On-site service is provided at sole discretion of MPC. A diagnostic determination for on-site service must be made by a MPC service technician prior to the provision of on-site service. On-site service is provided by a third-party service provider under a separate service contract between you and the service provider. Microsoft and Windows are registered trademarks of Microsoft Corporation. Product names of MPC products are trademarks or registered trademarks of MPC Computers, LLC. Other product names used in this publication are for identification purposes only and may be trademarks of their respective companies. DDR technology memory components are warranted under the applicable MPC limited warranty to function properly in the system in which they were factory-installed. MPC makes no warranty concerning the functionality of such components in any other system.